

OVERVIEW

Terraco Sil Excel is a ready-mixed, acrylic/silicone resin bound, textured coatings. It provides the unique combination of a quality architectural finish with outstanding economy through ease of application, a low material consumption rate and surface durability characterised by outstanding water repellence. Terracoat Sil Excel adheres to most exterior and interior surfaces including plywood, chipboard, anti-rust primed steel, gypsum and dry wall. Terracoat Sil Excel has been developed for use in areas of extreme climatic conditions such as the tropics, where high humidity is prevalent. Terracoat Sil Excel has enhanced water vapour permeability, mould resistance and has excellent dirt pick-up resistance.

PRODUCT GRADES/CODES

Excel 2mm	61413
Excel 3mm	61472

PROPERTIES

Terracoat Sil Excel is formulated from crushed and precisely graded fillers, a combination of acrylic and silicone resin binders and additives which gives it elastic properties, outstanding water repellence, water resistance and water vapour permeability, long life and durability against colour fading and pollution. Terracoat Sil Excel is a trowel applied texture giving an alpine scratch finish. Terracoat Sil Excel is available in 2 grain sizes, 2mm and 3mm, and in an attractive range of colours.

AREA OF USE

Terracoat Sil Excel is designed for use as the finish in the Terraco EIFS system. The coating performs equally well on interior surfaces of gypsum dry wall and chipboard and is widely used as a decorative ceiling and wall finish.

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with an appropriate filler.

Old surfaces: Before applying Terracoat Sil Excel to old surfaces, ensure the substrate is firm. First wash down the surface with a soda / water solution, rinse and allow to dry before repairing or applying the first coat.

PRIMING

Absorbent surfaces such as uncoated concrete and masonry should be primed with TERRACO Silprime. For previously painted surfaces P Primer should be used.

APPLICATION & CLEANING OF TOOLS

Trowel application is done using a steel trowel to lay on the material and a wetted plastic trowel is used to pattern the surface.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terraco Sil is supplied in 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Acrylic/silicone resin based textured coating.
Binder	Acrylic and silicone resins.
Thinning	Water if required.
Drying Time	3 - 4 hours.
Liquid Water Transmission Note (W24-Volume)	<0.15 kg/m ² h ^{0.5}
Water Vapour Permeability (Sd-value)	<0.10m
Adhesion	>2.0 N/mm ²
Colours	50 standard colours.
Storage	12 months in original unopened containers.

Grade	Specific Gravity	Viscosity ('000 cps.)	Material consumption (Kg / m ²)	Application method	Pack sizes (Kg.)
Excel 2mm	1.70	35-45	2.5-3.0	Trowel	25
Excel 3mm	1.70	35-45	3.5-4.5	Trowel	25

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
 Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 1 2819 045
 Fax: +353 (0) 1 2819 048
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terrakovostok.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0)2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820 101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com