

A photograph of a modern glass skyscraper facade, showing a grid of dark window frames and highly reflective glass panels that mirror the sky and surrounding buildings. The overall color palette is dominated by warm, golden-brown and blue tones.

# Silshine Metallic™

METALLIC LUSTRE TOPCOAT

*Decorative Metallic Finish*

*The House of Scandinavian Finishing Materials*

# Silshine Metallic™

## METALLIC LUSTRE TOPCOAT

Architects and designers are seeking a solution to create a metallic effect finish as an alternative to, or to complement, aluminium cladding where budget constraints play a role in the design elements of a new building or when modernising / renovating an existing building. **Silshine Metallic™** provides a optimal solution.

Silshine Metallic is a premium quality, mid-sheen, exterior masonry decorative topcoat finish based on acrylic and silicone polymers and pearlescent pigments, which provide a unique metallic lustre finish.

In line with Terraco's philosophy of building Green, this eco-friendly waterbased product, used as part of any of the Terraco EIFS Systems contributes to sustainable building practices and, in particular, to energy efficiency in buildings, which has become a key benchmark of a successful building design.

Terraco Silshine Metallic has excellent dirt pick-up resistance, weather resistance, durability and water repellency. The product is designed for application on pigmented exterior open-pore textured coatings where it significantly improves dirt pick-up resistance.



### Areas of Use

- Ideal for creating feature panels on exterior walls
- As a topcoat for acrylic textured surfaces
- As a topcoat on exterior masonry paint
- As a decorative finish to Terraco EIFS

### Features and Benefits

- Unique radiant metallic finish
- Water resistant
- Excellent dirt pick-up resistance
- Mould resistant



ENVIRONMENTALLY FRIENDLY



### SURFACE PREPARATION – New and Old Exterior Surfaces

#### • New surfaces

- Remove all dust, dirt, release oil, grease, and foreign matter as the surface must be clean, dry and sound.

#### • Old surfaces

- Use high pressure water with degreasing agent as a mist spray to wash down entire surface and allow to dry.
- Repair all cracks and delaminated textured areas as required.
- Prepare cleaned surface using Handycoat Exterior putty and allow to cure for 12 hours.

### Colour Range



Silver

Aluminium

Gold

Bronze

Copper

#### Note

- Other tailor made colours are available on request depending on the size of the project or architect requirements.
- Although every precaution has been taken to ensure the accuracy of the colours herein, due to the printing process they should be considered indicative.

### APPLICATION

#### New and Old Surfaces

- Apply the acrylic textured / smooth basecoats – Terracoat or Terrashield.
- Apply Silshine Metallic by roller or spray in two coats directly onto the prepared surface. Allow 2 to 4 hours drying time between coats.

#### EIFS System – As a Decorative Finish

- Silshine Metallic can be used as part of the decorative finishing coat in a Terraco EIFS System.
- Install Terraco EIFS system to the Styrobond Basecoat level. (See installation instructions for Terraco EIFS.)
- Apply one coat of P Primer or Terrabond A (1:5).

#### A) Textured Finish

- Apply an acrylic textured base coat and allow to dry.
- Apply Silshine Metallic by roller or spray in two coats directly onto the textured surface, allow 2 to 4 hours drying time between coats.

#### B) Smooth Finish (where the Silshine Metallic will be applied in smaller sized panels)

- Trowel apply one coat Styroskim Putty up to 1.5mm and allow to dry.
- Sand to achieve a smooth surface. The sanding dust must be thoroughly wiped off with wet cloth.
- Apply two coats of Terrashield directly onto the prepared surface, allow 2 to 4 hours drying time between coats.
- Apply Silshine Metallic by roller or spray in two coats on the Terrashield applied smooth surface, allow 2 to 4 hours drying time between coats.

#### Please note:

- Terraco recommends the use of a textured base coat as substrate imperfections will reflect through the product.
- Clean tools and equipment with water after use.

TECHNICAL DATA	
Consumption	0.25g/m <sup>2</sup>
Application	Roller or spray
Drying time	2-4 hours between coats depending on ambient conditions
Finish	Mid-sheen
Colours	Silver, Aluminium, Gold, Bronze, Copper
Packaging	15kg Plastic pails
Storage	12 months in original, unopened containers





[www.terraco.com](http://www.terraco.com)

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • ALGERIA • EGYPT • SOUTH AFRICA • JORDAN • UAE • PAKISTAN • THAILAND • VIETNAM • CHINA • KOREA

Technical Data Sheets and Material Safety Data Sheets are available from your Terraco representative or on [www.terraco.com](http://www.terraco.com). Although every precaution has been taken to ensure the accuracy of the colours and textures represented herein they should be considered indicative. Terraco does not warrant the accuracy of the information provided herein and all information is subject to change without notice.

© All rights reserved. Terraco Holdings Ltd.