

OVERVIEW

Handyprime Exterior is a ready mixed compound used to apply on uneven exterior surfaces to act as a filler/primer prior to the application of exterior paints and coatings. It equalises the surface porosity to ensure that the final coating will have an even and consistent appearance without sheen differences.

PROPERTIES

Handyprime Exterior is a waterbased coating based on pigments, resins and precisely graded crushed fillers. Handyprime Exterior has the following properties:

- Equalises absorption and texture variations on exterior surfaces.
- Quick and easy to apply by roller, spray or brush.
- Quick drying, can be over-coated in 4 hours.
- Can be coloured with pigments if required.

AREAS OF USE

Handyprime Exterior is designed for exterior use. It is applied on concrete and masonry surfaces where patching compounds were used and the surface requires equalisation prior to painting. Handyprime Exterior is over-painted with exterior paints and coatings.

PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed away. Also ensure that the surface is solid, free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be painted. All cracks, chips, voids and damages should be repaired with a filler prior to painting.

APPLICATION & CLEANING OF TOOLS

Stir well before use. Can be diluted with 5% water prior to use. Apply by roller, spray or brush at a rate of 200gs/m². One coat is normally sufficient but for highly absorbent surfaces a second coat may be required. The product will be touch dry in 30 minutes and can be over-coated after 1 hour. Do not apply at temperatures below 5oC.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Handyprime Exterior is supplied in 25kg plastic pails.

The paint should be stored in a clean, dry area, protected from direct sunlight and extreme heat or cold. Unopened containers can be stored for 12 months. Ensure that oldest material is used first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Exterior roller applied filler/primer.
Binders	Acrylic.
Consumption	150-250gs/m ² .
Viscosity	8,000cps
Specific Gravity	1.54
pH Value	8.0-8.5
Drying Time	2 hours.
Application Method	Spray, brush or roller.
Packaging	25kg plastic pails.
Storage	12 month in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
 Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
 Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terrakovostok.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com