

OVERVIEW

Handycoat All-Purpose is a ready-to-use filler and board jointing compound for most building surfaces, including sand/ cement render and gypsum board. It gives a high quality, even surface for painting. Handycoat All-Purpose is specially manufactured for the painter to repair and touch up surfaces, both old and new, prior to painting.

PROPERTIES

Handycoat All-Purpose is made from a selected blend of acrylic polymers and precisely graded fillers. It is:

- Easy to use
- Does not flake off
- Has high adhesion power
- Applicable up to 4mm in thickness
- Has high coverage
- Quick drying
- Vapour permeable

AREAS OF USE

When dry, Handycoat All-Purpose bonds extremely well to cementitious materials, gypsum, gypsum boards, sprayplasters, wood, galvanised steel lathing and all common building surfaces. Ideal as a gypsum board jointing compound and skimcoat, for patching hairline cracks in walls, ceilings, repairing damage to plaster/paint work, nail holes in woodwork, making good around door architrave's and along the top of skirting boards.

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered.

Old surfaces: Before applying to old surfaces, ensure the substrate is firm. First wash down the surface with a sugar soap solution, rinse and allow to dry before repairing or applying the primer.

APPLICATION & CLEANING OF TOOLS

Apply the filler in a thin even layer. If a thick coat is necessary, apply several thin layers, allowing to dry between layers. Lightly sand the final surface before painting, within 24 hour of application.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Handycoat All-Purpose is supplied in 5kg and 25kg plastic pails and 25kg plastic bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 9 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Ready mixed quick drying filler for construction surfaces
Binders	Acrylic copolymer.
Fillers	Fine precisely graded fillers.
Dilution	With water if required.
Coverage	0.5 -1.5kg/m ² depending on substrate conditions.
Specific Gravity	1.65-1.75
Viscosity	100,000 – 160,000 cps
Colour	Off-white.
Standard Compliance	ASTM C- 475
Toxicity	Non-toxic.
Packaging	5 and 25kg plastic pails, 25kg plastic bags
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

ALGERIA:

SARL Terraco Algeria

Tel: +213 (0)23 23 07 80
 Fax: +213 (0)23 23 07 80
 E-mail: terraco@terraco.dz
 Web: www.terraco.dz

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 1 2819 045
 Fax: +353 (0) 1 2819 048
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

CHINA:

Terraco Architectural Coatings China Co., Ltd.

Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terraco.kh.ru
 Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com