

## OVERVIEW

Handycoat Lite EZ-Skim is a ready-to-use interior filler and board skimming compound for most building surfaces, including sand/ cement render and gypsum board. It weighs up to 30% less than the conventional filler, provides lower shrinkage and is easier to sand. It gives a high quality, even surface for painting. Handycoat Lite EZ-Skim is specially manufactured for the painter to repair and touch up surfaces, both old and new, prior to painting.

## PROPERTIES

Handycoat Lite EZ-Skim is made from a selected blend of acrylic polymers and precisely graded fillers. Properties include:

- Easy to use
- Does not flake off
- Excellent adhesion
- Easy sanding
- High coverage rate
- Quick drying
- Vapour permeable
- Low shrinkage
- 30% lighter in weight

## AREAS OF USE

When dry, Handycoat Lite EZ-Skim bonds extremely well to cementitious materials, gypsum, gypsum boards, sprayplasters, wood, galvanised steel lathings and all common building surfaces. Handycoat Lite EZ-Skim is designed for skimming gypsum board, sand/cement render, concrete panels and lightweight concrete surfaces.

## PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered.

## APPLICATION & CLEANING OF TOOLS

Apply the filler in a thin even layer. If a thick coat is necessary, apply several thin layers, allowing to dry between layers. Lightly sand the final surface before painting, within 24 hour of application.

Clean tools and equipment with water after use.

## HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

## PACKAGING & STORAGE

Handycoat Lite EZ-Skim is supplied in 4kg and 18kg plastic pails and 18kg plastic bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

## TECHNICAL DATA

<b>Product</b>	Ready mixed, quick drying skimming compound, for construction surfaces.
<b>Binders</b>	Acrylic copolymer.
<b>Fillers</b>	Fine precisely graded fillers.
<b>Dilution</b>	With water if required.
<b>Coverage</b>	0.3 -1.0kg/m <sup>2</sup> depending on substrate conditions.
<b>Layer Thickness</b>	Max 2mm/ layer.
<b>Specific Gravity</b>	1.15
<b>Colour</b>	White.
<b>Toxicity</b>	Non-toxic.
<b>Packaging</b>	4kg and 18kg plastic pails, 18kg plastic bags
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

### CHINA:

**Terraco Architectural Coatings China Co., Ltd.**  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**Terraco Chemical (Shanghai) Co., Ltd.**  
 Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

### EGYPT:

**Terraco Egypt Chemical Industries S.A.E.**  
 Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

### JORDAN:

**Jordan Swedish Polymers Industrial Corp.**  
 Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

### IRELAND:

**Terraco Technical Centre, Ireland**  
 Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com

### PAKISTAN:

**Terraco Pakistan Pvt. Ltd.**  
 Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

### ROMANIA:

**Terraco Romania SRL**  
 Tel: +40 (0)749 203 133  
 Fax: +40 (0)318 148 810  
 E-mail: ahaque@terraco.com  
 Web: www.terraco.com

### RUSSIA:

**OOO Terraco Sweden Ltd, Russia**  
 Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terrakovostok.ru  
 Web: www.terraco.com

### SOUTH KOREA:

**Terraco Korea Co., Ltd**  
 Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

### THAILAND:

**Terraco Industry (Thailand) Limited**  
 Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

### TURKEY:

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
 Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

### UAE:

**Terraco UAE Ltd**  
 Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

### UK:

**ADDAGRIP**  
 Tel: +44 (0)1825 761 333  
 Fax: +44 (0)1825 768 566  
 E-mail: sales@addagrip.co.uk  
 Web: www.addagrip.co.uk / www.terraco.com

### VIETNAM:

**Terraco Vietnam Co., Ltd**  
 Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com