

## OVERVIEW

Terraprime GP is a highly developed specialist primer designed for application on gypsum plaster, which is absorbed deeply into the substrate to ensure excellent adhesion of subsequent paints and coatings. Terraprime GP is supplied as a clear acrylic emulsion.

## PROPERTIES

Aqueous acrylic copolymer emulsion with the following properties:

- Improves adhesion of paint to gypsum plaster
- Binds dusting substrates
- Reduces efflorescence
- Reduces surface alkalinity
- Easy to apply

## AREA OF USE

Terraprime GP is designed for application on all types of gypsum plaster to improve adhesion of paints and coatings.

## PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Terraco Handycoat.

## PREPARATION OF PRIMER

Thoroughly stir Terraprime GP until a homogenous liquid is formed.

## APPLICATION & CLEANING OF TOOLS

Apply liberally and evenly by brush or appropriate spray equipment and allow to dry. The surface is considered fully treated when a slight sheen is seen to appear on the surface. Depending upon the surface condition it may be necessary to apply a second coat. Terraprime GP should be painted/covered as soon as possible, to ensure optimum adhesion.

Clean tools and equipment with water after use.

## HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

## PACKAGING & STORAGE

Terraprime GP is supplied in 5kg and 20kg containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

## TECHNICAL DATA

<b>Product</b>	Aqueous acrylic co-polymer.
<b>Viscosity at 23 Degree</b>	500cps
<b>pH Value</b>	8 – 8.5
<b>Specific Gravity</b>	1.02
<b>Coverage</b>	0.08-0.10kg/m <sup>2</sup> depending on substrate condition.
<b>Packaging</b>	5kg and 20kg containers.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

### CHINA:

Terraco Architectural Coatings China Co., Ltd.  
Tel: +86 (0)20 8759 4742  
Fax: +86 (0)20 8526 8056  
E-mail: sales@terraco.com.cn  
Web: www.terraco.com.cn

### Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18  
Fax: +86 (0)21 625205 47  
Email: sales@terraco.com.cn  
Web: www.terraco.com.cn

### EGYPT:

#### Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58  
Fax: +20 (0)22 29184 80  
E-mail: terraco@terraco.com.eg  
Web: www.terraco.com.eg

### JORDAN:

#### Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751  
Fax: +962 (0)6 553 6560  
E-mail: terraco@nol.com.jo  
Web: www.terraco.jo

### IRELAND:

#### Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555  
Fax: +353 (0) 404 66654  
E-mail: technical-centre@terraco.com  
Web: www.terraco.com

### PAKISTAN:

#### Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8  
Fax: +92 (0)42 3529 70 55  
Email: terraco@terraco.pk  
Web: www.terraco.com

### ROMANIA:

#### Terraco Romania SRL

Tel: +40 (0)749 203 133  
Fax: +40 (0)318 148 810  
E-mail: ahaque@terraco.com  
Web: www.terraco.com

### RUSSIA:

#### OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237  
Fax: +7 (0)495 6273 881  
E-mail: adm@terraco.ru  
Web: www.terraco.ru

#### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563  
Fax: +7 (0)4212 410591  
E-mail: terracovostok@terracokhv.ru  
Web: www.terraco.com

### SOUTH KOREA:

#### Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551  
Fax: +82 (0)2 5671 771  
E-mail: terraco@terraco.co.kr  
Web: www.terraco.co.kr

### THAILAND:

#### Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58  
Fax: +66 (0)2 946 68 59  
E-mail: terraco@terraco.co.th  
Web: www.terraco.com

### TURKEY:

#### Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423  
Fax: +90 (0)222 236 0425  
E-mail: terraco@terraco.com.tr  
Web: www.terraco.com.tr

### UAE:

#### Terraco UAE Ltd

Tel: +971 (0)4 326 2699  
Fax: +971 (0)4 326 2733  
E-mail: terraco@terraco.ae  
Web: www.terraco.com

### UK:

#### ADDAGRIP

Tel: +44 (0)1825 761 333  
Fax: +44 (0)1825 768 566  
E-mail: sales@addagrip.co.uk  
Web: www.addagrip.co.uk / www.terraco.com

### VIETNAM:

#### Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100  
Fax: +84 (0)650 3 820 101  
E-mail: terraco@terraco.com.vn  
Web: www.terraco.com