

OVERVIEW

Terracoat Textured Coating is a range of ready-mixed acrylic textured coatings. It provides the unique combination of a quality architectural finish with outstanding economy through ease of application, a low material consumption rate and surface durability. Terracoat adheres to most exterior and interior surfaces including plywood, chipboard, anti-rust primed steel, gypsum dry wall, sand/cement render and concrete. Terracoat has been developed to withstand extreme climatic conditions such as desert climate and extreme cold.

PRODUCT GRADES/CODES

G	61310
BT	61460
Smooth	61320
Superfine	61330
Fine	61340
Normal/Standard	61350
Decor	61370
Coarse	61380
Suede	61463

PROPERTIES

Terracoat is formulated from crushed and precisely graded fillers, pure acrylic binders and additives which give it elastic properties, long life and durability against colour fading and pollution. Its rich texture and in-built flexibility helps cover defects and minor cracks in the substrate. Terracoat is available in a range of different texture grades and attractive colours. All grades of Terracoat are designed to withstand large temperature swings between day and night.

Terracoat G

Terracoat G is a low build roller applied lightly grained textured coating. Consumption rates are low making it a very economical finish.

Terracoat BT

Terracoat BT is a low build roller applied textured coating. It is finished using a long-haired brush to give a striated lined finish.

Terracoat Smooth

Terracoat Smooth is a low build roller applied lightly textured coating. Consumption rates are low making it a very economical finish.

Terracoat Superfine

Terracoat Superfine is a roller/spray applied texture which can be used in a wide range of finishes depending on the application method and material consumption. Finishes vary from fine spray to roller stucco.

Terracoat Fine

Terracoat Fine is a low to medium build pattern applied by spray or roller.

Terracoat Normal/Standard

Terracoat Normal/Standard is a medium build textured finish applied by spray. A medium build spray pattern is the most popular finish.

Terracoat Decor

Terracoat Decor is a high build textured finish applied by decorative roller or hopper gun. The most popular finishes are roller stucco and coarse spray pattern.

Terracoat Coarse

Terracoat Coarse is a coarse grained textured coating applied by spray.

Terracoat Suede

Terracoat Suede is a medium build trowel applied finish. It is finished using a plastic trowel to give a suede effect finish.

AREA OF USE

Terracoat Textured Coating is primarily designed for exterior facades and surfaces of buildings such as commercial and industrial complexes, office projects, factories, hospitals and housing developments.

Terracoat Textured Coating can be used on surfaces of concrete, cement rendering, lightweight concrete, fairfaced stonework, brickwork, blockwork, plywood, anti-rust primed steel and galvanised steel.

The coating performs equally well on interior surfaces of gypsum dry wall and chipboard and is widely used as a decorative ceiling and wall finish.

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with an appropriate filler

Old surfaces: Before applying Terracoat Textured Coating to old surfaces, ensure the substrate is firm. First wash down the surface with a soda / water solution, rinse and allow to dry before repairing or applying the first coat.

PRIMING

Prime surfaces with a coat of Penetrating Primer prior to application of Terracoat.

APPLICATION & CLEANING OF TOOLS

Spray application is done using a hopper gun and compressor, ensuring to mask off areas not requiring coating.

Roller application is done using a series of decorative rollers to achieve different textures.

Trowel application is done using a steel trowel to lay on the material and a wetted plastic trowel is used to pattern the surface.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terracoat is supplied in 20kg or 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Acrylic based textured coating.
Binder	Pure Acrylic.
Thinning	Water if required.
Drying Time	3 - 4 hours.
Toxicity	Non-toxic.
Flame Spread	Class 0 ASTM E84-81H
Colours	50 standard colours.
Storage	12 months in original unopened containers.

Grade	Specific Gravity	Viscosity ('000 cps.)	Material consumption (Kg / m ²)	Application method	Pack sizes (Kg.)
G	1.70	50-60	0,5-0,6	Roller, Brush	25
BT	1.55	20-25	0.6-0.8	Roller, Brush	25
Smooth	1.65	55-65	0,6-0,9	Roller	25
Superfine	1.45	50-60	0,6-3,5	Spray, Roller	20
Fine	1.65	50-60	1.0-1.2	Spray, Roller	25
Normal/Standard	1.65	50-60	1,5-2,0	Spray	25
Decor	1.65	55-65	2,5-3,5	Spray, Roller	25
Coarse	1.65	50-60	2.0-3.0	Spray	25
Suede	1.75	40-60	1.5-2.0	Trowel	25

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
Fax: +353 (0) 404 66654
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

ROMANIA:

Terraco Romania SRL

Tel: +40 (0)749 203 133
Fax: +40 (0)318 148 810
E-mail: ahaque@terraco.com
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terrakovostok.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820 101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com