

### OVERVIEW

Flexipave Readymixed is an acrylic based coating used for coating tennis courts and other recreational surfaces. It is fade resistant, waterproof and highly durable and protects underlying surface from weather and climatic conditions. It is designed for use on tennis courts as part of the Flexipave system to replace the requirement for blending Flexipave smooth with sand on site. Flexipave Readymixed is available in range of eight standard colours, special colours can be produced on request.

### PROPERTIES

Flexipave Readymixed is based on tough acrylic resins and fade resistant inorganic pigments which ensure long life and resistance to the elements. The product has the following properties:

- Water and weatherproof coating.
- Allows surface to breath while remaining strongly anchored to the substrate.
- Fast drying.
- Using fine mesh sand the speed of the court can be controlled.
- Tough, resilient coating.
- Algae resistant finish.

### AREA OF USE

Flexipave Readymixed is designed as an intermediate coat for the Flexipave System for levelling and coating to replace blending Flexipave Smooth with sand on site.

### PREPARATION OF SURFACE

Ensure dust, dirt and foreign matter are removed from the surface. Prepare substrate using the other compounds of the Flexipave System.

Flexipave patching Compound to level all major defects.

Flexipave Filler to fill all minor surface defects.

Flexipave concrete primer for priming concrete substrates.

### MIX DESIGN

Flexipave Readymixed is blended with up to 20% water prior to application.

### APPLICATION & CLEANING OF TOOLS

Coating application is done in two coats using a 1mt rubber squeegee. The first coat is applied in a perpendicular direction to the playing net and second and final coats are applied in a parallel direction. The material consumption of Flexipave Readymixed is 1kg/m<sup>2</sup>. A minimum of 2 hours should be left between coats.

Clean tools and equipment with water after use

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Flexipave Readymixed is supplied in 25kg pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

#### TECHNICAL DATA

<b>Product</b>	Acrylic tennis court coating.
<b>Binders</b>	Acrylic.
<b>Fillers</b>	Crushed and precisely graded fillers/sands
<b>Pigments</b>	Weather resistant pigments.
<b>Drying Time</b>	2 hours between coats.
<b>Specific Gravity</b>	1.55
<b>Colours</b>	Eight standard shades. Other colours are available on request.
<b>Consumption</b>	1kg/m <sup>2</sup>
<b>Packaging</b>	25kg pails.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

#### CHINA:

Terraco Architectural Coatings China Co., Ltd.  
Tel: +86 (0)20 8759 4742  
Fax: +86 (0)20 8526 8056  
E-mail: sales@terraco.com.cn  
Web: www.terraco.com.cn

#### Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18  
Fax: +86 (0)21 625205 47  
Email: sales@terraco.com.cn  
Web: www.terraco.com.cn

#### EGYPT:

#### Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58  
Fax: +20 (0)22 29184 80  
E-mail: terraco@terraco.com.eg  
Web: www.terraco.com.eg

#### JORDAN:

#### Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751  
Fax: +962 (0)6 553 6560  
E-mail: terraco@nol.com.jo  
Web: www.terraco.jo

#### IRELAND:

#### Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555  
Fax: +353 (0) 404 66654  
E-mail: technical-centre@terraco.com  
Web: www.terraco.com

#### PAKISTAN:

#### Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8  
Fax: +92 (0)42 3529 70 55  
Email: terraco@terraco.pk  
Web: www.terraco.com

#### ROMANIA:

#### Terraco Romania SRL

Tel: +40 (0)749 203 133  
Fax: +40 (0)318 148 810  
E-mail: ahaque@terraco.com  
Web: www.terraco.com

#### RUSSIA:

#### OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237  
Fax: +7 (0)495 6273 881  
E-mail: adm@terraco.ru  
Web: www.terraco.ru

#### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563  
Fax: +7 (0)4212 410591  
E-mail: terracovostok@terracokhv.ru  
Web: www.terraco.com

#### SOUTH KOREA:

#### Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551  
Fax: +82 (0)2 5671 771  
E-mail: terraco@terraco.co.kr  
Web: www.terraco.co.kr

#### THAILAND:

#### Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58  
Fax: +66 (0)2 946 68 59  
E-mail: terraco@terraco.co.th  
Web: www.terraco.com

#### TURKEY:

#### Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423  
Fax: +90 (0)222 236 0425  
E-mail: terraco@terraco.com.tr  
Web: www.terraco.com.tr

#### UAE:

#### Terraco UAE Ltd

Tel: +971 (0)4 326 2699  
Fax: +971 (0)4 326 2733  
E-mail: terraco@terraco.ae  
Web: www.terraco.com

#### UK:

#### ADDAGRIP

Tel: +44 (0)1825 761 333  
Fax: +44 (0)1825 768 566  
E-mail: sales@addagrip.co.uk  
Web: www.addagrip.co.uk / www.terraco.com

#### VIETNAM:

#### Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100  
Fax: +84 (0)650 3 820101  
E-mail: terraco@terraco.com.vn  
Web: www.terraco.com