

OVERVIEW

Terraco Ipekcy is a two tone paint effect designed for interior surfaces. It is created using a two-component decorative paint system, consisting of Ipekcy Basecoat and Ipekcy Topcoat. Ipekcy Basecoat is roller applied as the first coat in the Ipekcy finishing system, which once dry, is then partially over-coated using Ipekcy Topcoat applied with a natural sponge, thereby producing an attractive dual-sheen matt and silk finish.

PRODUCT GRADES/CODES

Basecoat	62221
Topcoat	62131

PROPERTIES

Ipekcy offers the advantage of being economical with its low material consumption rate, while at the same time producing a luxurious decorative finish which is available in a wide range of attractive shades. Ipekcy Basecoat/Topcoat are based on acrylic co-polymer resins and high quality pigments to ensure excellent colour opacity, brushability and washability. The finish has an attractive lustre and is ideal for high quality finishing works.

AREAS OF USE

Ipekcy can be applied on all non-porous, interior surfaces. It is ideal for decorating the interior surfaces of restaurants, galleries, hotel lobbies and residential homes. Ipekcy Basecoat/Topcoat is applied as a first coat in the Ipekcy decorative system. It is applied by roller and partially over coated using Ipekcy Finishcoat which is applied using a natural sponge. The effect is to produce a dual-sheen matt and silk finish.

PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed and scraped away. Also ensure that the surface is solid, free from salt, oil, grease and ridges. Protect all adjacent areas not to be painted. All cracks, chips, voids and damages should be repaired with TERRACO Handycoat Interior or EZ-Skim prior to painting.

PRIMING

Dusty and flaking surfaces should be primed with TERRACO Penetrating Primer.

APPLICATION & CLEANING OF TOOLS

The first coat is roller applied by diluting Ipekcy Basecoat with water at a ratio of 15%. After the first coat is dry, roller apply a second coat of Ipekcy Basecoat and allow to dry for 5-6 hours. Finally Ipekcy topcoat is sponge applied, after diluting with water at a ratio of 10%. To create the desired two tone Ipekcy effect, use a natural sponge. It is recommended that it is tested on a piece of cardboard prior to application for colour and textured pattern. Ipekcy Topcoat is then applied on the wall by dipping into the mixture in such a way as to obtain the required texture.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Ipekcy Basecoat is supplied in 20kg conipails and 5kg buckets.

The paint should be stored in a clean, dry area, protected from direct sunlight and extreme heat or cold. Ensure that oldest material is used first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Matt/silk paint finish.
Binder	Acrylic co-polymer.
Colours	20 standard colours, specials available on request.
Drying Time	1 - 2 hours.
Viscosity	Basecoat : 110 K.U. Topcoat : 100 K.U.
Specific Gravity	Basecoat : 1.40 Topcoat : 1.27
Consumption Rate	Ipekcy Basecoat: 6-8lt/m ² Ipekcy Topcoat : 18-20lt/m ²
Dilution	With water up to 0-20%.
Packaging	20kg conipails and 5kg buckets.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:
Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:
Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:
Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
 Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terrakovostok.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com