



OVERVIEW

EnviroTac 100 is a high quality polymer dispersion adhesive designed for use as a general purpose flooring adhesive. EnviroTac 100 offers a safe and environmentally friendly alternative for bonding a wide range of flooring systems including PVC sheet and foam backed carpets. EnviroTac 100 is easy to use and clean up is with water.

EnviroTac 100 is specially formulated without the use of solvents, formaldehyde and any other harmful chemical. EnviroTac 100 is a member of the Terraco ECOLIFE product group which ensures minimal environmental impact.

PROPERTIES

EnviroTac 100 is a water-borne acrylic adhesive with the following properties:

- Suitable for most types of floorings
- Solvent free compound
- Can be used for dry or wet fixing
- Easy to use
- High strength bonding
- Water clean-up
- Low odour
- Environmentally friendly

AREAS OF USE

Suitable for use with carpet having all types of backing including foam, jute, polypropylene and rubber latex. Also used for carpet tile, PVC tiles and PVC sheets. Suitable for use over wood, chipboard, concrete, screed and terrazzo.

PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are brushed and scraped away. Also ensure the floor is free from salts, oil, grease and ridges, and protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with appropriate filler.

APPLICATION & CLEANING OF TOOLS

Apply EnviroTac 100 using a suitable notched trowel. The adhesive is also suitable for using for a wet application method when used with porous floor coverings. For non-porous materials allow the adhesive to become touch dry. Bond floor covering and apply pressure to ensure the best possible bond.

Wet adhesive should be cleaned using clean water. Once dried the adhesive should be cleaned using hot soapy water and/or scraping.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

EnviroTac 100 is supplied in 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.


TECHNICAL DATA

Product	Multi-purpose flooring adhesive.
Binder	Acrylic.
Coverage	0.3-0.6kg/m ² .
Specific Gravity	1.15
VOC Level	<5g/ltr.
Viscosity	55,000cps
Solid %	55% ± 1%
Clean-up	Water.
pH Value	8-8.5 approx.
Packaging	25kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
 Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
 Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terrakovostok.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com