

### OVERVIEW

Tileshield HS is a water-borne high strength acrylic roof tile coating specially formulated for factory application on concrete roof tiles. It provides a long life protection and decoration and is available in an attractive range of fade resistant colours. Tileshield HS has excellent waterproof properties and will not peel even under the most extreme climatic conditions. Tileshield HS provides excellent protection against lichen, moss and mould. Tileshield HS provides a medium gloss sheen.

### PROPERTIES

Tileshield HS is based on pure acrylic resins, light fast pigments and adhesion promoting additives. The coating has following properties:

- Excellent adhesion to substrate
- Excellent UV resistance
- Excellent weather resistance
- Easy to apply, quick drying
- Excellent colour retention
- Resistant to lichen, moss and mould
- Tough scratch resistant finish

### AREAS OF USE

Tileshield HS is designed for application on concrete and cement based roof tiles. It is designed for use on production lines with or without oven drying facilities.

### PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter is brushed away. Also ensure that the surface is free from salt, oil, grease and dust.

### PRIMING

Prime surface with a coat of Penetrating Primer prior to application of Tileshield HS. Alternatively a dilute (50:50 with water) coat of Tileshield HS can be used as a primer.

### APPLICATION & CLEANING OF TOOLS

Tileshield HS can be applied by brush, roller or spray in two coat application. Allow first coat to dry for 2 to 4 hours before applying second coat.

Clean tools and equipment with water after use.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Tileshield HS is supplied in 20kg plastic pails.

Store containers in a clean, dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

**TECHNICAL DATA**

<b>Product</b>	Acrylic roof tile coating.
<b>Binder</b>	Acrylic.
<b>Pigments</b>	Lime and light fast.
<b>Gloss</b>	Mid sheen coating.
<b>Drying Time</b>	2 to 4 hours.
<b>Viscosity</b>	8,000cps
<b>Specific Gravity</b>	1.15
<b>pH Value</b>	8-8.5
<b>Consumption</b>	150-250 gars/m <sup>2</sup> /coat.
<b>Packaging</b>	20kg plastic pails.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

**CHINA:**

**Terraco Architectural Coatings China Co., Ltd.**  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**Terraco Chemical (Shanghai) Co., Ltd.**  
 Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**EGYPT:**

**Terraco Egypt Chemical Industries S.A.E.**  
 Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

**JORDAN:**

**Jordan Swedish Polymers Industrial Corp.**  
 Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

**IRELAND:**

**Terraco Technical Centre, Ireland**  
 Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com

**PAKISTAN:**

**Terraco Pakistan Pvt. Ltd.**  
 Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

**RUSSIA:**

**OOO Terraco Sweden Ltd, Russia**  
 Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

**OOO Terraco Vostok Ltd**

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terraco.khv.ru  
 Web: www.terraco.com

**SOUTH KOREA:**

**Terraco Korea Co., Ltd**  
 Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

**THAILAND:**

**Terraco Industry (Thailand) Limited**  
 Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

**TURKEY:**

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
 Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

**UAE:**

**Terraco UAE Ltd**  
 Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

**UK:**

**ADDAGRIP**  
 Tel: +44 (0)1825 761 333  
 Fax: +44 (0)1825 768 566  
 E-mail: sales@addagrip.co.uk  
 Web: www.addagrip.co.uk / www.terraco.com

**VIETNAM:**

**Terraco Vietnam Co., Ltd**  
 Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com