

OVERVIEW

Terraco Superwood is a high-quality, durable, water based, exterior decorative wall finish, which replicates the appearance of wood. It is resistant to harsh climatic conditions and specially formulated for use in regions of extreme climatic conditions. The final appearance of the system depends on the application tool used to create a “wood look”. Superwood is available in a range of colours and can be applied over suitably prepared sand-cement render, concrete or sheathing board system.

PRODUCT GRADES/CODES

Superwood BC	61875
Superwood TC	61874
Retarder Solution	61876

PROPERTIES

Superwood is a wall finish system for interior and exterior application to create wood like effect with color combination of Superwood BC and Superwood TC with the following properties:

- Extremely resistant to weather conditions
- Suitable for interior-exterior application
- Resistant to UV, salt laden air and industrial pollutants.
- Excellent adhesion
- Unique appearance

AREA OF USE

Superwood can be applied over levelled surfaces to replicate wood appearance in the following areas:

- Ideal for feature walls/elements on a building elevations.
- Suitable for cementitious rendered walls, concrete and cement fiber boards.
- As a decorative finish to Terraco EIFS.

PREPARATION OF SURFACE

New / Old surfaces: Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Handycoat Exterior (for exterior application) or Handycoat Fine/ Handycoat interior Stucco Putty (for interior application). Sand down the surface to ensure it is smooth and even. Remove all dust.

APPLICATION & CLEANING OF TOOLS

Apply two coats of Superwood BC uniformly by brush, roller or spray, leaving drying time of 4-6 hours between the coats. Ensure that second coat application of Superwood BC gives uniform colour to the substrate. Allow final coat of Superwood BC to dry overnight.

Ensure that surface temperature is below 25°C prior to application of Superwood TC.

Apply Superwood TC by brush/fine roller followed by pattern creation, using different designing tools, to create a “wood like” effect, according to approved site mock-up sample. Allow to dry for 24-48 hours. A 20-30% retarder solution can be added in Superwood TC colours to extend the application time of Superwood TC.

Clean tools and equipment with water after use.

1. In order to achieve desired appearance, it is strongly recommended to work with experienced and professional painters and decorators.
2. Superwood system is designed for creating feature areas replicating wood effect. It is recommended that the area to be coated should be divided into smaller panel sizes using masking tape joints or grooves for a better uniform finish as continuous application over large areas is extremely difficult to achieve.
3. It is recommended that the area should be prepared with tape joints. This allows any touch-ups/repairs required to the appearance to be done easily.
4. Do not apply if rain is expected over the next 24 hours (for each coat application).
5. Drying time depends on site conditions.

HEALTH & SAFETY

Avoid prolonged contact with skin. In case of contact with eyes, rinse with plenty of water and consult a doctor. Keep out of reach of children. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Superwood BC and FC are supplied in 3.6 litre and 18 litre plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TECHNICAL DATA

Product	Acrylic based decorative paint system
Binders	Pure acrylic copolymer
Thinning	If necessary, with water
	If necessary, 20-30% retarder solution can be used
Colour	Superwood BC: According to Colour Chart Superwood TC: According to Colour Chart
Application	By rollers and various designing tools
Consumption	Superwood BC: 0.200 -0.300 l/m ² Superwood TC: 0.100-0.200 l/m ²
Drying time	Superwood BC: 4-6 hours Superwood TC: 1-2 hours
Packaging	Superwood BC – TC: 3.6 litre and 18 litre plastic containers
Storage	12 months in original, unopened containers

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

For technical enquiries please contact your nearest Terraco representative:

ALGERIA:

SARL Terraco Algeria
Tel: +213 (0)23 23 07 80
Fax: +213 (0)23 23 07 80
E-mail: terraco@terraco.dz
Web: www.terraco.dz

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 1 2819 045
Fax: +353 (0) 1 2819 048
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terrakovostok.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP
Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820 101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com