

OVERVIEW

Handycoat 3-in-1 is a versatile finishing material for interior construction surfaces which can be used for skimming, priming and painting depending on the dilution ratio used. It is used directly from the drum for skimming at a consumption rate of 0.5-0.8kg/m². For painting, it is diluted with 25-30% water and applied at a rate of 150-200grs/m²/coat. For priming, it is diluted with 30-35% water and applied at a rate of 100-150grs/m².

PROPERTIES

Handycoat 3-in-1 is a waterbased coating based on pigments, resins and precisely graded crushed fillers. Handycoat 3-in-1 has the following properties:

- Versatile multi-functional product
- Quick and easy to apply by roller, spray or brush
- Quick drying, can be over-coated in two hour
- Can be coloured with pigment pastes if required

AREAS OF USE

Handycoat 3-in-1 is designed for interior use. Direct from drum, it is used as a skimcoat putty to repair and smoothen walls and ceilings prior to priming and painting.

Handycoat 3-in-1 can be diluted with 25-30% water and used as an interior paint for walls and ceilings.

A dilution of 30-35% water, creates an excellent compound for priming masonry and gypsum board.

PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed away. Also ensure that the surface is solid, free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be painted. All cracks, chips, voids and damages should be repaired with a filler prior to painting.

APPLICATION & CLEANING OF TOOLS

As a skimcoat putty, apply with spatula in 1-2 coats and sand surfaces to remove any surface defects.

As a primer or paint, dilute with required water and apply by roller or brush

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Handycoat 3-in-1 is supplied in 25kg plastic bags.

The compound should be stored in a clean, dry area, protected from direct sunlight and extreme heat or cold. Unopened containers can be stored for 12 months. Ensure that oldest material is used first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Multi-purpose putty-paint-primer compound.
Binders	Acrylic.
Fillers/Pigments	Calcium carbonate/inorganic oxides.
Viscosity	100,000cps
Specific Gravity	1.70
pH Value	8.0-8.5
Drying Time	2-4 hours
Packaging	25kg plastic bags
Storage	9 month in original unopened containers.

Application	Material consumption (Kg / m ²)	Dilution Rate	Application method
Putty	0.5-0.8	0-5%	Trowel/spatula
Paint	0.15-0.2	25-30%	Brush/roller
Primer	0.12-0.15	30-35%	Brush/roller

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:
Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:
Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:
Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
 Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terraco.khn.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com