



### OVERVIEW

Handyplus is a decorative effect for walls for interior use, which gives the wall an attractive pearlescent lustre. Handyplus is used as a pearlescent topcoat in combination with other decorative effects from Terraco such as Handytex, Decolite and Terracoat InteriorTex.

Handyplus is specially formulated without the use of solvents, formaldehyde and any other harmful chemical. Handyplus is a member of the Terraco ECOLIFE product group which ensures minimal environmental impact.

### PROPERTIES

Handyplus is a blend of acrylic polymers and pearlescent pigments with the following properties:

- Easy to use.
- Provides an attractive pearlescent lustre.
- Strong water resistant finish.
- Can be used to topcoat most finishes/emulsion paints.
- Low odour
- Environmentally friendly

### AREAS OF USE

Can be used on most interior finished surfaces such as painted walls, textured finished walls etc..

### PREPARATION OF SURFACE

If applying as a topcoat on newly decorated wall finishes, allow base material to dry overnight. If applying on previously painted surfaces ensure that the surface is clean and free of any dust or grease.

### APPLICATION & CLEANING OF TOOLS

Handyplus is supplied as a gel and designed for application by trowel or spatula.

Clean tools and equipment with water after use.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Handyplus is supplied in 1kg and 5kg plastic containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

### TECHNICAL DATA

<b>Product</b>	Pearlescent effect for walls.
<b>Binder</b>	Acrylic.
<b>Thinning</b>	Water if required.
<b>Drying Time</b>	1 - 2 hours.
<b>Specific Gravity</b>	1.03
<b>Viscosity</b>	37,000 cps.
<b>VOC Level</b>	<5g/m <sup>3</sup> / litre.
<b>Material Consumption</b>	0.15-0.2 kg /m <sup>2</sup> .
<b>Application Method</b>	Trowel / Spatula.
<b>Flame Spread</b>	Class 0 ASTM E84-95b
<b>Colours</b>	Range of 10 attractive pearlescent tones.
<b>Packaging</b>	1kg and 5kg plastic containers.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

#### CHINA:

**Terraco Architectural Coatings China Co., Ltd.**  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

#### Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

#### EGYPT:

#### Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

#### JORDAN:

#### Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

#### IRELAND:

#### Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com

#### PAKISTAN:

**Terraco Pakistan Pvt. Ltd.**  
 Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

#### ROMANIA:

**Terraco Romania SRL**  
 Tel: +40 (0)749 203 133  
 Fax: +40 (0)318 148 810  
 E-mail: ahaque@terraco.com  
 Web: www.terraco.com

#### RUSSIA:

**OOO Terraco Sweden Ltd, Russia**  
 Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

#### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terrakovostok.ru  
 Web: www.terraco.com

#### SOUTH KOREA:

**Terraco Korea Co., Ltd**  
 Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

#### THAILAND:

**Terraco Industry (Thailand) Limited**  
 Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

#### TURKEY:

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
 Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

#### UAE:

**Terraco UAE Ltd**  
 Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

#### UK:

**ADDAGRIP**  
 Tel: +44 (0)1825 761 333  
 Fax: +44 (0)1825 768 566  
 E-mail: sales@addagrip.co.uk  
 Web: www.addagrip.co.uk / www.terraco.com

#### VIETNAM:

**Terraco Vietnam Co., Ltd**  
 Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com