

OVERVIEW

Terracoat Stone is a stone effect exterior acrylic render with excellent weather resistant properties. Terracoat Stone is designed to be applied by spray and gives the appearance of "hammer finished granite". Terracoat Stone is available in a range of attractive shades.

PROPERTIES

Terracoat Stone is supplied in paste form, formulated from natural stone chippings dispersed in a synthetic resin. The combination provides an excellent protective vapour-permeable coating. It has high resistance to atmospheric corrosion as well as to fading.

AREAS OF USE

Exterior and interior facades of concrete, cement rendering, EIFS finishing system and wood; on buildings such as commercial complexes, hospitals, industrial complexes, commercial office projects and housing developments.

PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter is brushed and scraped away. Also ensure that the surface is solid, free from salts, oil, grease and ridges. All cracks, chips, voids and damages should be repaired with filler prior to application of Terracoat Stone. Terraco Handycoat Exterior or Terramix are recommended.

PRIMING

On the cleaned surface apply a coat of Penetrating Primer.

APPLICATION & CLEANING OF TOOLS

Terracoat Stone is supplied ready to use in paste form and is applied using a hopper gun. Using relatively high pressure, an even coat is applied to the entire surface at a rate of approx. 2.0kg/m². The pressure is then reduced and a further coat is applied at a rate of approximately 1.0kg/m². This can be left as a textured "hammer finish" or lightly knocked down with a trowel to produce a pitted look. The coating is allowed to dry for 24 to 48 hours after which a clear coat of Terracoat Topcoat is applied.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terracoat Stone is supplied in 25kg containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Stone effect exterior coating.
Consumption	Approximately 2.8-3.2/m ² .
Coat Thickness	2mm
Weather Resistance	Weather resistant and washable.
Colour	Terracoat Stone is available in a range of natural shades.
Binder	Acrylic binders.
Filler Material	Natural stone chippings/marble.
Additives	Chemical resistant additives, plasters and adhesion-improving additives.
Durability	Life expectancy of 10 years depending upon climatic conditions if correctly applied.
Application	By hopper gun.
Packaging	25kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:
Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:
Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:
Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
 Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terrakovostok.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com