

OVERVIEW

CemAdmix AF is a dry mix additive for blending with Terraco product such as Terrafix, Terragrout, Styrobond DP, Styrofix, Terol, Terramix and other dry-mix cementitious compounds to accelerate setting time and allow work to proceed at low temperatures. The addition of CemAdmix AF improves adhesion and gives high early strength at low temperatures. CemAdmix AF does not contain any chlorides hence is resistant to corrosion.

PROPERTIES

Dry-mix products blended with Cemadmix AF exhibit the following properties:

- Workable down to -10°C
- Set acceleration
- Higher early strength
- Improved substrate adhesion

AREAS OF USE

CemAdmix AF is an anti-freezer additive designed for use in Terraco Terrafix, Terragrout, Styrobond DP, Styrofix, Terol, Terramix, plaster and other dry-mix cementitious compounds.

USAGE RATIO

CemAdmix AF is blended with water in the following ratios and used as the gauging water/mix to blend with dry-mix compound.

Temp	Water	: CemAdmix AF
0°C	7ltr	: 1kg
-5 °C	5ltr	: 1kg
-10 °C	3ltr	: 1kg

MIXING

CemAdmix AF blends easily with water and the resultant mix is blended with the dry-mix compound using a drill agitator for 3 minutes.

APPLICATION & CLEANING OF TOOLS

Use the mixed compound as per relevant data sheet. Mixed material should be used within 1 hour. Do not re-temper material with extra water.

Clean tools and equipment with water immediately after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

CemAdmix AF is supplied in 5kg and 20kg plastic drums.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Set control accelerator for cementitious dry mix compounds.
Appearance	Clear, pale yellow mobile liquid.
SG	1.35 ± 0.05
Viscosity	<50cps
Mixing Ratio	Temp Water : CemAdmix AF 0°C 7ltr : 1kg -5 °C 5ltr : 1kg -10 °C 3ltr : 1kg
Packaging	5kg and 20kg plastic drums.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:
Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:
Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:
Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
Fax: +353 (0) 404 66654
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
Tel: +40 (0)749 203 133
Fax: +40 (0)318 148 810
E-mail: ahaque@terraco.com
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terrakovostok.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP
Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com