

OVERVIEW

Tileshield HS Plus is a water-borne high strength acrylic roof tile coating specially formulated for factory application on concrete roof tiles. It provides a long life protection and decoration and is available in an attractive range of fade resistant colours. Tileshield HS Plus has excellent waterproof properties and will not peel even under the most extreme climatic conditions. Tileshield HS Plus provides excellent protection against lichen, moss and mould. Tileshield HS Plus provides a medium gloss sheen. Tileshield HS Plus provides enhanced abrasion resistance.

PRODUCT GRADES/CODES

Oven Dry	61842
Air Dry	61843

PROPERTIES

Tileshield HS Plus is based on pure acrylic resins, light fast pigments and adhesion promoting additives. The coating has following properties:

- Excellent adhesion to substrate
- Excellent UV resistance
- Excellent weather resistance
- Easy to apply, quick drying
- Excellent colour retention
- Resistant to lichen, moss and mould
- Enhanced abrasion resistance

AREAS OF USE

Tileshield HS Plus is designed for application on concrete and cement based roof tiles. It is designed for use on production lines with or without oven drying facilities.

PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter is brushed away. Also ensure that the surface is free from salt, oil, grease and dust.

PRIMING

Prime surface with a coat of Penetrating Primer prior to application of Tileshield HS Plus. Alternatively a dilute (50:50 with water) coat of Tileshield HS Plus can be used as a primer.

APPLICATION & CLEANING OF TOOLS

Tileshield HS Plus can be applied by brush, roller or spray in two coat application. Allow first coat to dry for 2 to 4 hours before applying second coat.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Tileshield HS Plus is supplied in 20kg plastic pails.

Store containers in a clean, dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	High scratch resistance acrylic roof tile coating.
Binder	Acrylic.
Pigments	Lime and light fast.
Gloss	Mid sheen coating.
Drying Time	2 to 4 hours.
Viscosity	8,000cps
Specific Gravity	1.15
pH Value	8-8.5
Consumption	150-250 gars/m ² /coat.
Packaging	20kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 1 2819 045
Fax : +353 (0) 1 2819 048
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terraco.khv.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP
Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com