

ANTIQUE STUCCO

INTERIOR MARBLE EFFECT COATING

62330

OVERVIEW

Antique Stucco is an acrylic based Venetian stucco suitable for use on most interior surfaces. Antique Stucco can be applied to produce both traditional and modern effects by adjusting the application methods. The final effect is a translucent highly polished finish. Antique Stucco can be tinted using Terraco "one-shot" colourants.

PROPERTIES

Antique Stucco is an acrylic based paste of inert fillers and pigments, with the following properties:

- Highly decorative effect
- Non-combustible
- High gloss polished finish
- Environmentally friendly

AREAS OF USE

Antique Stucco can be used on most interior surfaces. Ideal finishing for restaurants, galleries, hotel lobbies, etc.

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Terraco Handycoat Exterior.

Old surfaces: Before applying to old surfaces, ensure the substrate is firm. First wash down the surface with a sugar soap solution, rinse and allow to dry before repairing or applying the primer.

PRIMING/SKIMCOAT

Prime surfaces with a coat of Penetrating Primer prior to application of Antique Stucco.

Apply a coat of Handycoat by trowel to level and prepare substrate for Antique Stucco application.

APPLICATION & CLEANING OF TOOLS

Many different patterns can be achieved using various application tools. For an Venetian Stucco effect apply initial coat of material with a wide trowel Subsequent coats are applied using a fine blade spatula, building up a number of layers over a period of time. The colour may be varied for a more dramatic effect. When the material is drying, polish the surface using a white steel blade, until the required sheen is achieved.

For a contemporary effect, Antique Stucco is applied by spatula in patch work application utilising the translucency of the product to create the effect. Polish using a buffing cloth, while the Antique Stucco is drying.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Antique Stucco is supplied in 6kg and 15kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.



ANTIQUE STUCCO

INTERIOR MARBLE EFFECT COATING

62330

TECHNICAL DATA

Product	Marble effect coating.
Binder	Acrylic.
Drying Time	30 - 60 minutes.
Viscosity	100,000cps
Specific Gravity	1.45-1.50
Flame Spread	Class 0 ASTM E84-95b
Material Consumption	0.5-1.2kg/m² depending on desired effect.
Application Method	By trowel, spatula.
Colour	Using Terraco "one-shot" colourant paste.
Packaging	6kg and 15kg plastic pails.
Storage	12 months in original unopened containers.
	-

For technical enquiries please contact your nearest Terraco representative:

CHINA:

${\bf Terraco\ Architectural\ Coatings\ China\ Co.,\ Ltd.}$

Tel: +86 (0)20 8759 4742 Fax: +86 (0)20 8526 8056 E-mail: sales@terraco.com.cn Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18 Fax: +86 (0)21 625205 47 Email: sales@terraco.com.cn Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58 Fax: +20 (0)22 29184 80 E-mail: terraco@terraco.com.eg Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751 Fax: +962 (0)6 553 6560 E-mail: terraco@nol.com.jo Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555 Fax: +353 (0) 404 66654

E-mail: technical-centre@terraco.com

Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8 Fax: +92 (0)42 3529 70 55 Email: terraco@terraco.pk Web: www.terraco.com

ROMANIA:

Terraco Romania SRL

Tel: +40 (0)749 203 133 Fax: +40 (0)318 148 810 E-mail: ahaque@terraco.com Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237 Fax: +7 (0)495 6273 881 E-mail: adm@terraco.ru Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563 Fax: +7 (0)4212 410591

E-mail: terracovostok@terracokhv.ru

Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551 Fax: +82 (0)2 5671 771 E-mail: terraco@terraco.co.kr Web: www.terraco.co.kr

THAILAND

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58 Fax: +66 (0)2 946 68 59 E-mail: terraco@terraco.co.th Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423 Fax: +90 (0)222 236 0425 E-mail: terraco@terraco.com.tr Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699 Fax: +971 (0)4 326 2733 E-mail: terraco@terraco.ae Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0) 1825 761 333 Fax: +44 (0) 1825 768 566 E-mail: sales@addagrip.co.uk

Web: www.addagrip.co.uk / www,terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100 Fax: +84 (0)650 3 820101 E-mail: terraco@terraco.com.vn Web: www.terraco.com