



OVERVIEW

Terrabontile is a ready-mixed acrylic coating for interior use. It is applied by hopper gun to give a bubble texture spray pattern. Terrabontile adheres to most interior surfaces including plywood, chipboard, gypsum dry wall, sand/cement render and concrete. Terrabontile is top-coated with interior emulsion paint to give an attractive interior textured surface.

Terrabontile is specially formulated without the use of solvents, formaldehyde and any other harmful chemical. Terrabontile is a member of the Terraco ECOLIFE product group which ensures minimal environmental impact.

PROPERTIES

Terrabontile is formulated from crushed and precisely graded fillers, acrylic binders and additives that ensure excellent adhesion to the substrate.

Terrabontile has the following properties:

- Easy spray application
- Good adhesion to most substrates
- Attractive finish
- Quick drying
- Low odour
- Environmentally friendly

AREAS OF USE

Terrabontile is designed for interior surfaces of buildings such as commercial and industrial complexes, office projects, and factories. Terrabontile can be used on surfaces of concrete, cement rendering, lightweight concrete, fairfaced stonework, brickwork, blockwork and plywood. The coating is widely used as a decorative ceiling finish.

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are brushed and scraped away. Also ensure the surfaces are free from salts, oil, grease and ridges, and protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Handycoat Interior.

Old surfaces: Before applying Terrabontile to old surfaces, ensure the substrate is firm. First wash down the surface with a soda/water solution, rinse and allow to dry before repairing or applying the first coat.

PRIMING

Priming of new work is not necessary but in order to stabilise a surface which shows signs of dusting, a coat of penetrating primer should be used.

APPLICATION & CLEANING OF TOOLS

Spray application is done using a hopper gun and compressor, ensuring to mask off areas not requiring coating. Apply to the required bubble density and size by adjusting the air pressure and the nozzle size. Allow to dry overnight before finishing surface with 2 coats of emulsion paint.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Product is supplied in 25kg containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

| | |
|---------------------------|--|
| Product | Acrylic based interior texturing compound. |
| Binder | Acrylic co-polymer. |
| Thinning | Water if required. |
| Drying Time | 3 - 4 hours. |
| Toxicity | Non-toxic. |
| Viscosity | 90,000 cps. |
| Specific Gravity | 1.75 |
| VOC Level | <5 gm/ltr |
| Coverage (m2/ kg) | 0.5-1.50 kg/m ² . |
| Application Method | Spray. |
| Flame Spread | Class 0 ASTM E84-81H |
| Packaging | 25kg plastic pails. |
| Storage | 12 months in original unopened containers. |

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:
Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:
Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:
Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

ROMANIA:

Terraco Romania SRL
 Tel: +40 (0)749 203 133
 Fax: +40 (0)318 148 810
 E-mail: ahaque@terraco.com
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terrakovostok.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com