

### OVERVIEW

Renu-Tile HS is a water-borne high strength acrylic roof tile coating specially designed for refreshing previously coated concrete roof tiles. It provides a long life protection and decoration and is available in an attractive range of fade resistant colours. Renu-Tile HS has excellent waterproof properties and will not peel even under the most extreme climatic conditions. Renu-Tile HS provides excellent protection against lichen, moss and mould. Renu-Tile HS provides a medium gloss sheen.

### PROPERTIES

Renu-Tile HS is based on pure acrylic resins, light fast pigments and adhesion promoting additives. The coating has following properties:

- Excellent adhesion to substrate
- Excellent UV resistance
- Excellent weather resistance
- Easy to apply, quick drying
- Excellent colour retention
- Resistant to lichen, moss and mould
- Tough scratch resistant finish

### AREAS OF USE

Renu-Tile HS is designed for application on previously coated roof tiles which require a freshen-up.

### PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter is brushed away. Remove any mould using Terraco Sterilising Solution. Also ensure that the surface is free from salt, oil, grease and dust.

### PRIMING

Prime surface with a coat of Penetrating Primer prior to application of Renu-Tile HS. Alternatively a dilute (50:50 with water) coat of Renu-Tile HS can be used as a primer.

### APPLICATION & CLEANING OF TOOLS

Renu-Tile HS can be applied by brush, roller or spray in two coat application. Allow first coat to dry for 2 to 4 hours before applying second coat.

Clean tools and equipment with water after use.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Renu-Tile HS is supplied in 20kg plastic pails.

Store containers in a clean, dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

#### TECHNICAL DATA

<b>Product</b>	Acrylic roof tile coating.
<b>Binder</b>	Acrylic.
<b>Pigments</b>	Lime and light fast.
<b>Gloss</b>	Mid sheen coating.
<b>Drying Time</b>	2 to 4 hours.
<b>Viscosity</b>	8,000cps
<b>Specific Gravity</b>	1.15
<b>pH Value</b>	8-8.5
<b>Consumption</b>	150-250 gars/m <sup>2</sup> /coat.
<b>Packaging</b>	20kg plastic pails.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

#### CHINA:

**Terraco Architectural Coatings China Co., Ltd.**  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

#### Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

#### EGYPT:

#### Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

#### JORDAN:

#### Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

#### IRELAND:

#### Terraco Technical Centre, Ireland

Tel: +353 (0) 1 2819 045  
 Fax : +353 (0) 1 2819 048  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com

#### PAKISTAN:

**Terraco Pakistan Pvt. Ltd.**  
 Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

#### RUSSIA:

#### OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

#### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terraco.kv.ru  
 Web: www.terraco.com

#### SOUTH KOREA:

#### Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

#### THAILAND:

#### Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

#### TURKEY:

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
 Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

#### UAE:

#### Terraco UAE Ltd

Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

#### UK:

#### ADDAGRIP

Tel: +44 (0)1825 761 333  
 Fax: +44 (0)1825 768 566  
 E-mail: sales@addagrip.co.uk  
 Web: www.addagrip.co.uk / www.terraco.com

#### VIETNAM:

#### Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com