

### OVERVIEW

Handycoat Exterior Coarse is a ready-to-use high build filler for use on all common building surfaces. It gives a high quality, even surface for painting. Handycoat Exterior Coarse is specifically manufactured for the painter to repair exterior and interior surfaces, both new and old, prior to painting. It is designed for high build repairs by hand application. Unlike conventional fillers, Handycoat Exterior Coarse has elastic properties, does not flake off, is permanent and retains its adhesion.

### PROPERTIES

Handycoat Exterior Coarse is formulated using acrylic binders and precisely graded fillers. Properties include:

- Tough durable filler
- Weather resistant
- Alkali resistant
- Easy to apply
- Quick drying
- High crack resistance
- Excellent adhesion
- Suitable for deep repairs

### AREAS OF USE

Handycoat Exterior Coarse is suitable for exterior as well as interior surfaces. When dry, Handycoat Exterior Coarse is weather resistant and bonds extremely well to cementitious materials, gypsum, gypsum boards, sprayplaster and wood.

Handycoat Exterior Coarse is ideal for use as a jointing compound for cement fibre-board to embed glass fibre scrim.

### PREPARATION OF SURFACE

Ensure dust, dirt, foreign matter are brushed away. Ridges and form oil should be removed.

When applying filler to old painted surfaces first wash down with soda / water solution, rinse and allow to dry before filling.

To stabilise a surface which shows signs of dusting or flaking, the use of Penetrating Primer is recommended.

### APPLICATION & CLEANING OF TOOLS

Apply the filler in a thin, even layer; if the area under repair requires a thick coat, apply several thin layers, allowing each layer to dry before adding the next. Lightly sandpaper over the dry final surface before painting preferably within 8 hours of application.

Clean tools and equipment with water after use.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Handycoat Exterior Coarse is supplied in 25kg and 5kg plastic containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

### TECHNICAL DATA

<b>Product</b>	Ready mixed quick drying filler for exterior surfaces.
<b>Binders</b>	Styrene acrylate.
<b>Fillers</b>	Precisely graded fillers up to 0.3mm.
<b>Dilution</b>	With water if required.
<b>Coverage</b>	1.7kg/m <sup>2</sup> /mm
<b>Layer Thickness</b>	Maximum 3mm.
<b>Specific Gravity</b>	1.75
<b>Colour</b>	White
<b>Toxicity</b>	Non-toxic.
<b>Packaging</b>	25kg and 5kg pails.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

#### CHINA:

**Terraco Architectural Coatings China Co., Ltd.**  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**Terraco Chemical (Shanghai) Co., Ltd.**  
 Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

#### EGYPT:

**Terraco Egypt Chemical Industries S.A.E.**  
 Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

#### JORDAN:

**Jordan Swedish Polymers Industrial Corp.**  
 Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

#### IRELAND:

**Terraco Technical Centre, Ireland**  
 Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com

#### PAKISTAN:

**Terraco Pakistan Pvt. Ltd.**  
 Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

#### ROMANIA:

**Terraco Romania SRL**  
 Tel: +40 (0)749 203 133  
 Fax: +40 (0)318 148 810  
 E-mail: ahaque@terraco.com  
 Web: www.terraco.com

#### RUSSIA:

**OOO Terraco Sweden Ltd, Russia**  
 Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

#### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terrakovostok.ru  
 Web: www.terraco.com

#### SOUTH KOREA:

**Terraco Korea Co., Ltd**  
 Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

#### THAILAND:

**Terraco Industry (Thailand) Limited**  
 Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

#### TURKEY:

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
 Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

#### UAE:

**Terraco UAE Ltd**  
 Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

#### UK:

**ADDAGRIP**  
 Tel: +44 (0)1825 761 333  
 Fax: +44 (0)1825 768 566  
 E-mail: sales@addagrip.co.uk  
 Web: www.addagrip.co.uk / www.terraco.com

#### VIETNAM:

**Terraco Vietnam Co., Ltd**  
 Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com