

OVERVIEW

Flexipave Resurfacer is an acrylic based filler for fine filling and smoothing of asphalt substrates prior to Flexipave Coating application. It is designed for filling minor defects and hairline cracks. Flexipave Resurfacer has elastic properties and will retain its adhesion permanently.

PROPERTIES

Flexipave Resurfacer is a quick drying paste formulated using acrylic binders and precisely graded fillers. It is blended with clean dry sand prior to use.

- Quick drying
- Easy to use
- Excellent adhesion
- Water resistant

AREAS OF USE

For filling or repairing fine cracks and surface defects in asphalt when using the Flexipave System in order to produce a surface of the highest quality for final finishing.

PREPARATION OF SURFACE

Remove all oil, grease, dirt, foreign substance and loose particles. Use Flexipave Patching Compound for major repairs or levelling purposes.

MIXING

Flexipave Resurfacer is always blended with sand and water in the following ratio:

Resurfacer 1pt

Silica sand (0.1-0.3mm) 0.6pt

Water 0.4pt

APPLICATION & CLEANING OF TOOLS

Apply the compound in a thin, even layer, using a squeegee. More than one coat may be required. Lightly sandpaper over the dry final surface before finishing preferably within 8 hours of application.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Flexipave Resurfacer is supplied in 15kg plastic pails and 200kg steel drums.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Quick drying synthetically bound filler for asphalt surfaces.
Filler	Precisely graded marble powder.
Binder	Acrylic
Mixing Ratio	Resurfacer 1pt : Sand (0.1-0.3mm) 0.6pt : Water 0.4pt
Density	1.10
Colour	Black, green.
Application	By squeegee.
Consumption	0.2-0.3kg/m ² /coat
Cleaning of Tools	With water.
Packaging	15kg plastic pails and 200kg steel drums.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 1 2819 045
 Fax : +353 (0) 1 2819 048
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terraco.kv.ru
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com