

### OVERVIEW

Flexipave Filler is an acrylic based ready-to-use filler for fine filling and smoothing of substrates prior to Flexipave Coating application. It is designed for filling minor defects and hairline cracks. Flexipave Filler has elastic properties and will retain its adhesion permanently.

### PROPERTIES

Flexipave Filler is a quick drying ready-mixed paste formulated using acrylic binders and precisely graded fillers. Due to its special formulation, a high quality surface is obtained on concrete and asphalt surfaces. When dry, Flexipave Filler is weather resistant and bonds extremely well to the substrate.

### AREAS OF USE

For filling or repairing fine cracks and surface defects in concrete, asphalt when using the Flexipave System in order to produce a surface of the highest quality for final finishing.

### PREPARATION OF SURFACE

Remove all oil, grease, dirt, foreign substance and loose particles. Use Flexipave Concrete Primer for concrete surfaces. Use Flexipave Patching Compound for major repairs or levelling purposes.

### APPLICATION & CLEANING OF TOOLS

Apply the compound in a thin, even layer, using a spatula. More than one coat may be required. Lightly sandpaper over the dry final surface before painting preferably within 8 hours of application.

Clean tools and equipment with water after use.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Flexipave Filler is supplied in 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

**TECHNICAL DATA**

<b>Product</b>	Quick drying synthetically bound ready-mixed putty.
<b>Filler</b>	Precisely graded marble powder.
<b>Binder</b>	Acrylic
<b>Dilution</b>	With water if required.
<b>Density</b>	1.70
<b>Colour</b>	White
<b>Application</b>	By spatula.
<b>Consumption</b>	0.5-1.0kg/m <sup>2</sup> depending upon thickness/substrata condition.
<b>Cleaning of Tools</b>	With water.
<b>Packaging</b>	25kg plastic pails.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

**CHINA:**

**Terraco Architectural Coatings China Co., Ltd.**  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**Terraco Chemical (Shanghai) Co., Ltd.**

Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**EGYPT:**
**Terraco Egypt Chemical Industries S.A.E.**

Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

**JORDAN:**
**Jordan Swedish Polymers Industrial Corp.**

Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

**IRELAND:**
**Terraco Technical Centre, Ireland**

Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com

**PAKISTAN:**
**Terraco Pakistan Pvt. Ltd.**

Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

**ROMANIA:**
**Terraco Romania SRL**

Tel: +40 (0)749 203 133  
 Fax: +40 (0)318 148 810  
 E-mail: ahaque@terraco.com  
 Web: www.terraco.com

**RUSSIA:**
**OOO Terraco Sweden Ltd, Russia**

Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

**OOO Terraco Vostok Ltd**

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terrakovostok.ru  
 Web: www.terraco.com

**SOUTH KOREA:**
**Terraco Korea Co., Ltd**

Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

**THAILAND:**
**Terraco Industry (Thailand) Limited**

Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

**TURKEY:**
**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**

Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

**UAE:**
**Terraco UAE Ltd**

Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

**UK:**
**ADDAGRIP**

Tel: +44 (0)1825 761 333  
 Fax: +44 (0)1825 768 566  
 E-mail: sales@addagrip.co.uk  
 Web: www.addagrip.co.uk / www.terraco.com

**VIETNAM:**
**Terraco Vietnam Co., Ltd**

Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com