

### OVERVIEW

Terrapaste P22 is a high strength paste type acrylic tile adhesive with non-slump characteristics. Terrapaste P22 complies with requirements as per EN12004 and passes all test requirements for D2T classified adhesives. Terrapaste P22 is suitable for interior walls for use on all types of masonry substrates such as gypsum board and sand /cement render. Terrapaste P22 is specially formulated without the use of solvents, formaldehyde and any other harmful chemical. Terrapaste P22 is a member of the Terraco ECOLIFE product group which ensures minimal environmental impact.

### PROPERTIES

- Excellent adhesion
- Easy workability
- Non-slump
- Environmentally friendly ECOLIFE formulation.

### AREAS OF USE

High strength non-slump ceramic and mosaic tile adhesive for use on all type of interior walls and floors such as gypsum board, cement based render, tile backer board, sound painted surfaces and wooden substrates.

### PREPARATION OF SURFACE

**New surfaces:** Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Terraco Handycoat Exterior.

**Old surfaces:** Before applying to old surfaces, ensure the substrate is firm. First wash down the surface with a sugar soap solution, rinse and allow to dry before repairing or applying the primer.

### APPLICATION & CLEANING OF TOOLS

Apply Terrapaste P22 in a layer approximately 3mm thick to the surface with the smooth side of a notched trowel. Pull the trowel through the applied layer using the notched side. Push and twist the tiles into place so that full adherence is

obtained. Fix tiles before the adhesive layer is surface dry. Plan work accordingly. Do not allow a "skin" to form on the surface of applied adhesive.

Clean tools and equipment with water after use.

### CLEANING OF TILES

Remove excess adhesive from the face of the tile with a wet sponge before the adhesive dries.

### GROUTING

Refer to Terragrout data sheet for details.

### EXPANSION JOINTS

Expansion joints, when necessary, should be incorporated at the design stage.

### HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

### PACKAGING & STORAGE

Terrapaste P22 is supplied in 5 and 25 kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

**TECHNICAL DATA**

<b>Product</b>	High strength, non-slump tile adhesive in paste form.
<b>Filler</b>	Precisely graded crushed dolomite/calcite.
<b>Binder</b>	Acrylic.
<b>Additives</b>	Contains additives to improve plasticity and adhesion.
<b>Colour</b>	Natural white.
<b>Quality Type</b>	Passes tests as per D2T/EN12004.
<b>Tensile Adhesion</b>	Standard condition : EN1324 >1.0N/mm <sup>2</sup> Heat aging : EN1324 >1.0N/mm <sup>2</sup> After water immersion : EN1324 >0.5N/mm <sup>2</sup>
<b>Application Temperature</b>	5-35°C
<b>Consumption</b>	Trowel No. 4: 1.5-2.0 kg/m <sup>2</sup> Trowel No. 5: 2.0-2.5 kg/m <sup>2</sup>
<b>Adjustability Time</b>	>45 minutes.
<b>Open Time</b>	>30 minutes
<b>Ready to Grout</b>	24 hours
<b>Ready for Use</b>	7 days
<b>Packaging</b>	5kg and 25kg plastic pails.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

**CHINA:**

**Terraco Architectural Coatings China Co., Ltd.**  
Tel: +86 (0)20 8759 4742  
Fax: +86 (0)20 8526 8056  
E-mail: sales@terraco.com.cn  
Web: www.terraco.com.cn

**Terraco Chemical (Shanghai) Co., Ltd.**

Tel: +86 (0)21 621020 48 / 18  
Fax: +86 (0)21 625205 47  
Email: sales@terraco.com.cn  
Web: www.terraco.com.cn

**EGYPT:**
**Terraco Egypt Chemical Industries S.A.E.**

Tel: +20 (0)22 29184 53 / 57 / 58  
Fax: +20 (0)22 29184 80  
E-mail: terraco@terraco.com.eg  
Web: www.terraco.com.eg

**JORDAN:**
**Jordan Swedish Polymers Industrial Corp.**

Tel: +962 (0)6 553 8751  
Fax: +962 (0)6 553 6560  
E-mail: terraco@nol.com.jo  
Web: www.terraco.jo

**IRELAND:**
**Terraco Technical Centre, Ireland**

Tel: +353 (0) 404 66555  
Fax: +353 (0) 404 66654  
E-mail: technical-centre@terraco.com  
Web: www.terraco.com

**PAKISTAN:**

**Terraco Pakistan Pvt. Ltd.**  
Tel: +92 (0)42 3529 70 56-8  
Fax: +92 (0)42 3529 70 55  
Email: terraco@terraco.pk  
Web: www.terraco.com

**ROMANIA:**

**Terraco Romania SRL**  
Tel: +40 (0)749 203 133  
Fax: +40 (0)318 148 810  
E-mail: ahaque@terraco.com  
Web: www.terraco.com

**RUSSIA:**

**OOO Terraco Sweden Ltd, Russia**  
Tel: +7 (0)495 9212 237  
Fax: +7 (0)495 6273 881  
E-mail: adm@terraco.ru  
Web: www.terraco.ru

**OOO Terraco Vostok Ltd**

Tel: +7 (0)4212 410563  
Fax: +7 (0)4212 410591  
E-mail: terracovostok@terrakovostok.ru  
Web: www.terraco.com

**SOUTH KOREA:**

**Terraco Korea Co., Ltd**  
Tel: +82 (0) 2 5611 551  
Fax: +82 (0)2 5671 771  
E-mail: terraco@terraco.co.kr  
Web: www.terraco.co.kr

**THAILAND:**

**Terraco Industry (Thailand) Limited**  
Tel: +66 (0)2 946 68 56 / 58  
Fax: +66 (0)2 946 68 59  
E-mail: terraco@terraco.co.th  
Web: www.terraco.com

**TURKEY:**

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
Tel: +90 (0)222 236 0423  
Fax: +90 (0)222 236 0425  
E-mail: terraco@terraco.com.tr  
Web: www.terraco.com.tr

**UAE:**

**Terraco UAE Ltd**  
Tel: +971 (0)4 326 2699  
Fax: +971 (0)4 326 2733  
E-mail: terraco@terraco.ae  
Web: www.terraco.com

**UK:**

**ADDAGRIP**  
Tel: +44 (0)1825 761 333  
Fax: +44 (0)1825 768 566  
E-mail: sales@addagrip.co.uk  
Web: www.addagrip.co.uk / www.terraco.com

**VIETNAM:**

**Terraco Vietnam Co., Ltd**  
Tel: +84 (0)650 3 820 100  
Fax: +84 (0)650 3 820101  
E-mail: terraco@terraco.com.vn  
Web: www.terraco.com