

OVERVIEW

Terol Granite Glitter is a superior quality decorative mineral render which when finished gives a glitter effect and is ideal for use on EIFS to achieve glitter grain finish in a thin coat layer of only 3mm. Terol Granite Glitter is easy and quick to apply and is finished smooth with steel trowels. Terol Granite Glitter is available in a range of 16 attractive granite effects.

PROPERTIES

- Glitter grain finish (3mm)
- Mineral based render
- Low dirt pick-up
- Designed for finishing EIFS
- Long life expectancy
- Breathable coating system
- Superior weather resistance
- Easy to apply

AREA OF USE

Terol Granite Glitter is designed for application on EIFS surfaces where a glitter effect is required. It is also suitable for use on conventional masonry substrates.

PREPARATION OF SURFACE

Ensure all dust, dirt and foreign matter are brushed and scraped away. Also ensure surface is solid, free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be coated. All surface defects should be repaired prior to application of Terol Granite Glitter, with Terramix.

MIXING PROPORTIONS

Terol Granite Glitter is delivered in powder form and simply needs mixing with water using a high-speed mixer for approximately 3 minutes, or a slow mixer for 15 minutes. For small quantities, mixing can be carried out with an agitator driven by a power drill. After mixing, allow to stand for 5 minutes, remix and use.

APPLICATION & CLEANING OF TOOLS

For a uniform finish, ensure that the water content and mixing times are consistent. Prepared material should be used with 4 hours of mixing. Apply mixed material by trowel or spray to a thickness of 3-4mm and level with a steel trowel. Allow to "set-up" and float with a steel trowel to achieve a smooth surface. Allow to cure overnight, saturate the surface with water and treat with a dilute hydrochloric acid wash to expose the decorative aggregate. Repeat treatment if required. Wash off surface immediately to remove any excess acid..

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terol Granite Glitter is supplied in 25kg paper sacks.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TECHNICAL DATA

Product	Glitter grain effect mineral render.
Colour	Available in 16 standard colours
Filler	Crushed, precisely graded extenders.
Binder	Blend of special cements, lime and organic binders.
Pigments	Characterised as fast to light, lime, salt and cement.
Additives	Plasticizers, water-retention and adhesion-improving additives.
Tensile adhesion strength	>0.3 N/mm ²
Material Consumption	4-8 kg/m ²
Packaging	25kg paper sacks.
Storage	12 months in original unopened container.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 1 2819 045
Fax: +353 (0) 1 2819 048
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terrakovostok.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP
Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com