

////// TERRACO®



handymate® flexible filler

paintable filler for gaps
between masonry & wood

- ✓ ideal for gaps along skirting boards & door frames
- ✓ suitable for interior & exterior use
- ✓ long life flexibility & adhesion
- ✓ 30% more coverage than conventional fillers



handymate[®] flexible filler

paintable filler for gaps between masonry & wood

handymate[®] flexible filler

is a high-performance, ready-to-use product designed for application between wood and masonry where a permanently flexible joint is required. It is suitable for interior and exterior use as well as bathrooms and kitchens.


Handymate Flexible Filler will surface dry in 1-2 hours depending on thickness and temperature. Suitable for gaps up to 20mm in width & 10 mm in depth. Ideal for gaps along window & door frames and along skirting boards. Paintable with emulsion paint when dry



instructions




1) Ensure surfaces and holes are clean, dry and free from dust and loose material. Prime any exposed nail / screw heads with a suitable metal primer prior to application.



2) If applying from a tube, cut nozzle to correct bead size according to required gap width - squeeze and move steadily along the length of the gap ensuring an even and continuous bead.



3) If applying from a bucket, use a thin-blade putty knife or spatula.



4) The filler surface can be levelled with a damp sponge or cloth to achieve an even finish.

Please note: Do not expose to rain or water until fully dry. Remove any excess material before it dries.

Clean tools with water after use. Store in a cool, dry place. Protect from frost and extremes of temperature. Check packaging for expiry date. Once opened, packs may have limited storage life.

For information & application videos

www.handymate.com