

**//// TERRACO®**



# Handycoat® Exterior

READY-MIXED EXTERIOR FILLER



**HIGH  
STRENGTH**



# Handycoat<sup>®</sup> Exterior

## Tough and Durable Finish.

Handycoat Exterior is a ready-mixed filler used for skimming surfaces and as a patching compound for filling wall holes, joints & repairing hairline cracks. It is formulated for exterior use to ensure high strength, exceptional weather and crack resistance to provide a durable finish. Unlike conventional fillers, Handycoat Exterior has elastic properties, does not flake off and retains its adhesion.

When using Handycoat Exterior, it is easier to prepare surfaces and get an even surface for painting when repairing and touching up old or new surfaces.



## WHY CHOOSE HANDYCOAT EXTERIOR?

### WEATHER RESISTANT

The product is specially formulated for exterior use. It demonstrates excellent resistance to water. This greatly enhances the systems durability in the most extreme weather conditions.

### EASY TO APPLY

Handycoat Exterior is designed for applicators to repair and touch up surfaces in an easy and efficient way.

### EVEN SURFACE FOR PAINTING

Handycoat Exterior provides superior surface preparation with excellent whiteness and a uniform finish for a lower paint consumption.



## OTHER FEATURES AND BENEFITS

- Quick drying compared to conventional fillers resulting in faster application and saving time
- Good alkali and crack resistance enhance durability of the system
- High adhesion power prevents flaking thus reducing the need for repair

## AREAS OF USE

- Cementitious Materials
- Concrete
- Precast Concrete
- Cement Boards
- Mineral Boards
- Exterior Gypsum Boards
- Other Common Building Surfaces

## HANDYCOAT EXTERIOR IS PERFECT FOR

- Patching hairline cracks
- Repairing damages in plaster & paint work
- Jointing cement and mineral boards
- Filling nail holes
- Filling honeycomb in concrete substrate
- Repairing defects in exposed concrete
- Skimming of façade walls



## HOW TO USE

- 1 Apply the filler in a thin even layer
- 2 If a thick coat is necessary apply several thin layers
- 3 Allow to dry between layers
- 4 Lightly sand the final surface within 4 hours before painting

\*For detailed usage instructions, please refer to the Technical Data Sheet

## TECHNICAL DATA

Dilution	With a small quantity of water if required
Coverage	0.5 -1.5kg/m <sup>2</sup> depending on substrate conditions
Layer Thickness	Maximum thickness 1mm/layer
Specific Gravity	1.65 +/-0.05
Colour	White
Packaging	5 and 25 kg plastic pails
Storage	12 months in original unopened containers



[www.terraco.com](http://www.terraco.com)

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • ALGERIA • EGYPT  
JORDAN • UAE • THAILAND • VIETNAM • CHINA • KOREA