

**////// TERRACO<sup>®</sup>**



# Handycoat<sup>®</sup> Lite Exterior

LIGHTWEIGHT READY-MIXED EXTERIOR FILLER



**LIGHT  
WEIGHT**





# Handycoat<sup>®</sup> Lite Exterior

**Up to 30% lighter than conventional fillers.**

Handycoat Lite Exterior is formulated with special raw materials which make it up to 30% lighter than conventional fillers without compromising on volume.

Handycoat Lite Exterior is easier to carry and transport reducing stress on the body of the applicator. It is easy to apply and sand providing a faster and more comfortable application experience.



## WHY CHOOSE HANDYCOAT LITE EXTERIOR?

### HIGH STRENGTH

Handycoat Lite Exterior is designed to be tough and durable. The elastic properties with low shrinkage provide good resistance to cracking and flaking. The product has excellent adhesion which ensures long life of the system.

### WEATHER RESISTANT

The product is designed for exterior use. It has excellent resistance to water, UV, dirt and other harsh weather elements. This greatly enhances life cycle of the system by making it last long regardless of weather conditions.

### EASY TO APPLY & SAND

Handycoat Lite Exterior is easy to apply and sand providing a faster and more comfortable application experience.



## OTHER FEATURES AND BENEFITS

- Easy to apply and sand providing a faster and more comfortable application experience
- Quick drying properties enables faster output and quicker job completion
- Higher flexibility for use on multiple substrates as skim coat or board jointing compound
- Good alkali resistance enhances life of the system

## AREAS OF USE

- Cementitious Materials
- Concrete
- Precast Concrete
- Cement Boards
- Exterior Gypsum Boards
- Wood Panel Boards such as OSB
- Other Mineral Boards
- All Common Building Surfaces

## HANDYCOAT LITE EXTERIOR IS PERFECT FOR

- Patching hairline cracks in walls, ceilings and soffits
- Repairing damaged plasterwork and paintwork
- Jointing cement and mineral boards
- Filling nail holes
- Filling honeycomb in concrete substrate
- Repairing defects in woodwork and exposed concrete



## HOW TO USE

- 1 Apply the filler in a thin even layer
- 2 If a thick coat is necessary apply several thin layers
- 3 Allow to dry
- 4 Lightly sand before painting

\*For detailed usage instructions, please refer to the Technical Data Sheet

## TECHNICAL DATA

Dilution	With water if required
Coverage	0.3 -1.0kg/m <sup>2</sup> depending on substrate conditions
Layer Thickness	Maximum 2mm
Specific Gravity	1.10
Colour	White
Packaging	4kg and 18kg pails
Storage	12 months in original unopened containers



[www.terraco.com](http://www.terraco.com)

SWEDEN • UK • IRELAND • RUSSIA • TURKEY • ALGERIA • EGYPT  
JORDAN • UAE • THAILAND • VIETNAM • CHINA • KOREA