

////// TERRACO®

fills up to 20mm in one go



drillable
when dry

handymate® deep-fill

non-shrink deep gap & crack filler

- ✓ ideal for gaps around light switches, sockets & deeper repairs
- ✓ suitable for interior & exterior use
- ✓ highly durable
- ✓ easy to apply & sand



handymate[®] deep-fill


non-shrink deep gap & crack filler

handymate[®] deep-fill is a ready-to-use filler designed for filling deep holes up to 20mm in one application without slumping. It can be sanded to a smooth finish and will not shrink or crack.

Handymate Deep-Fill will surface dry in 1-2 hours depending on thickness and temperature. Suitable for interior and exterior repairs of plaster, gypsum board and masonry up to 20mm in thickness. Ideal for deeper repairs around light sockets & window frames. Handymate Deep-Fill is drillable and will accept nails and screws once fully dry. Paintable with emulsion paint when dry.




instructions



1) Ensure surfaces and holes are clean, dry and free from dust and loose material. Prime any exposed nail / screw heads with a suitable metal primer prior to application.



2) Mix Handymate Deep-Fill to a smooth consistency before use.



3) Apply in layers of up to 20mm per coat allowing each layer to dry before overcoating.



4) Lightly sand to a fine finish when dry.

Please note: Do not expose to rain or water until fully dry.

Clean tools with water after use. Store in a cool, dry place. Protect from frost and extremes of temperature. Check packaging for expiry date. Once opened, packs may have limited storage life.

For information & application videos

www.handymate.com